

# **Useddairyequipment**

## **Inline high shear dissolver**

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| Offer number                   | : 25-28-02                                         |
| Make                           | : Scanima                                          |
| Type                           | : SFM 200-in-line                                  |
| Capacity                       | : 200 liter                                        |
| Serial number                  | : 10450-06                                         |
| Year of manufacturing          | : 2006                                             |
| Power motor                    | : 22,0 kW - 400 V - 38,5 A - 50 Hz<br>- 2.950 rpm. |
| Total dimensions ( l x w x h ) | : 110 x 63 x 90 cm.                                |
| Weight                         | : +-355 kg.                                        |
| Condition of the machine       | : Good                                             |
| Location                       | : The Netherlands                                  |
| Terms of delivery              | : FCA                                              |



Inline high shear dissolver / dispergator mixer. Impellor diameter: 198 mm. Cilinder diameter: 200 mm, screen hole diameter 4 mm (height cilinder 78 mm). With manual recirculation bypass butterfly valve. Shaft speed: 2800 rpm. Flushed seal. Connections: 1x 3" SMS and 2x 2,5" Din..



Inline-Dissolver / Dispergator mit hoher Scherkraft. Impellerdurchmesser: 198 mm. Zylinderdurchmesser: 200 mm, Sieblochdurchmesser 4 mm (Zylinderhöhe 78 mm). Mit manuellem Bypass-Absperrventil. Wellendrehzahl: 2800 U/min. Gespülte Dichtung. Anschlüsse: 1x 3" SMS und 2x 2,5" DIN.



Mélangeur disperseur / disperseur en ligne à haut cisaillement. Diamètre de la turbine : 198 mm. Diamètre du cylindre : 200 mm, diamètre du trou de tamis : 4 mm (hauteur du cylindre : 78 mm). Avec vanne papillon de dérivation manuelle pour recirculation. Vitesse de rotation de l'arbre : 2 800 tr/min. Garniture rincée. Raccords : 1 SMS 3" et 2 DIN 2,5".



Inline high-shear dissolver / dispergator mixer. Waaierdiameter: 198 mm. Cilinderdiameter: 200 mm, zeefgat diameter 4 mm (hoogte cilinder 78 mm). Met handmatige recirculatie-bypass vlinderklep. Assnelheid: 2800 tpm. Flushed seal. Aansluitingen: 1x 3" SMS en 2x 2,5" Din.



Mezclador disolvedor / dispersor de alto cizallamiento en línea. Diámetro del impulsor: 198 mm. Diámetro del cilindro: 200 mm, diámetro del orificio del tamiz: 4 mm (altura del cilindro: 78 mm). Con válvula de mariposa de recirculación manual. Velocidad del eje: 2800 rpm. Sello de purga. Conexiones: 1 SMS de 3" y 2 DIN de 2,5".

**For more information check our website: [www.useddairyequipment.com](http://www.useddairyequipment.com)**

PLEASE NOTE: We do not intentionally send our offers to any unwilling recipients.

If you have been incorrectly included in our mailing list, or do not wish to receive further offers from us, please reply with [REMOVE](#) as subject, and use the same mail address that we have send to. Please accept our apologies for any inconvenience caused!