

USED DAIRY EQUIPMENT

EMAIL:
SALES@USED DAIRY EQUIPMENT.COM
 WEBSITE:
WWW.USED DAIRY EQUIPMENT.COM

Cooking-mixing installation

QUOTE NR	26-20-02
MAKE	Steiner Apparatebau GmbH
TYPE	LK 1000
CAPACITY	1250 liter
SERIAL NR	10-1355
YEAR	2010
POWER	1.5 kW
DIMENSIONS (CM)	540x430x450
CONDITION OF MACHINE	Good
LOCATION AND TERMS	FCA Lopik



Interested in staying updated? Scan the QR code to sign up for our mailing list and receive the latest news and offers.



Cooking-mixing installation

Fruit Cooking-mixing unit for viscose products like fruit jams. Installation existing out of: SS support framework with working platform and stairs, mix cooking tank, trolley-bin elevator for loading with safety fence, 2x standard norm trolley, 1x norm trolley with build on mixer, balance vessel with pump, control panel, swingbend panel, valves and piping. Previously used for making red berry compote.

Steiner mixtank double jacketed and insulated with centered scraper agitator, motor: 1,5 kW - 3,6 A - 2.860 rpm - n2: 10 rpm- 50 Hz. Full scraping coverage along the sides with spring-loaded teflon (PTFE) scrapers. Stirring: speed adjustable (via Danfoss frequency convertor), time and interval adjustable.

Heating with saturated steam via jacket or via direct steam injection, 4 steam injection ports; two ports at the front and two at the back. 1x E&H temperature sensor to be able to check the filling temperature. Diessel flowmeter with control valve for water.

Elevator max 300 kg- can be operated on the floor and on platform. With position sensor on top. SS fencing with door with safety sensor.

Trolley mixer in height adjustable with agitator for dissolving. Trolley capacity: 200 liters, mobile with lifting strips.